KUJBA

Refrigerated counter-Depth 60cm-Universal

One-piece AISI 304 stainless steel body. Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm.Depth 60 cm.For shelves 32,5x46 cm.3 doors.Control panel with digital thermometer - thermostat.



((

Genera	inform	ation
Genera	Intorm	arion

Supplier/producer 's name	SAGI
Series	Universal
Supplier's model identifier	KUJBA
Category	counter cabinet
Туре	refrigerated counter
Line	catering - depth 60 cm

Technical features

Temperature ranges, °C	0/+10	
Energy Efficiency Class	С	
Energy consumption, kWh/24h	2,433	
Energy consumption/year, kWh/a	888	
Method for energy consumption	EN 22041	
Energy Efficiency Index	38,21	
Net usable volume, lt	209	
Volume, gross, lt	353	
Climate class	5 (+40°C, 40% R.H.)	
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C	
Refrigerant/GWP	R290/3	
Refrigerant charge, kg	0,07	
LWA dB(A)	50	
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability	
Defrosting	automatic	

Refrigerated counter-Depth 60cm-Universal





Refrigerated counter-Depth 60cm-Universal

KUJBA



KUJBA		
Evaporation of condense drain	automatic	
Refrigeration power at -10°C W	465	
Frequency/voltage	230V 1N~ / 50Hz	
Electric power, kW	0,28	
onstruction features		
Structure	one-piece structure with rounded internal corners	
External material	AISI 304 stainless steel	
Internal material	AISI 304 stainless steel	
Internal bottom	with rounded corners	
Insulation thickness, mm	60	
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac	
Internal structure	AISI 304 stainless steel grid-supporting rack	
Positions (n.)/spaced, mm	11/40,5	
Evaporator	with an anti-corrosion treatment	
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condense	
Feet	stainless steel AISI 304, adjustable in height	
Height of feet, mm	140 ÷ 200	
Equipped with	3 doors	
ontrol and functions		
Kinf of control	thermometer-thermostat	
Display	digital	
Alarms	optical and acoustical	
andard		
Key-lock	optional	
Shelf's dimensions, cm	32,5x46	
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf for section	
imensions and weights		
Packing (LxDxH), cm	192x66x100	
Dimensions (LxDxH), cm	185x60x98,5	

Dim

Packing (LxDxH), cm	192x66x100
Dimensions (LxDxH), cm	185x60x98,5
Gross Weight (kg)	138
Net Weight (kg)	126



