

KUB2A

Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body.Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm.Depth 70 cm.GN 1/1.With doors and drawers.Control panel with digital thermometer - thermostat.



CE

General information

eneral information	
Supplier/producer 's name	SAGI
Series	Universal
Supplier's model identifier	KUB2A
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1
chnical features	
Temperature ranges, °C	0/+10
Energy Efficiency Class	C
Energy consumption, kWh/24h	2,973
Energy consumption/year, kWh/a	1085
Method for energy consumption	EN 22041
Energy Efficiency Index	46,29
Net usable volume, lt	217
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it Angelo Po S.p.a. reserves the right to make product changes and cannot b



Refrigerated counter-GN1/1-AISI 304-Universal

o S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or error 1/2 PRINTED 29/07/2022 12.05.43

KUB2A



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condense
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	doors and drawers
Drawers, type: 1/2	2

Control and functions

Gross Weight (kg)

Net Weight (kg)

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical
Standard	
Key-lock	optional
Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
Dimensions and weights	
Packing (LxDxH), cm	192x76x100
Dimensions (LxDxH), cm	185x70x98,5

160

148

