

F 58 Chest Freezer



Chest Freezer Derby

Versatile, practical, good-looking and efficient: all you expect from a Chest Freezer

The superior quality of the Derby brand can also be proved through its Chest Freezer line. They are resistant and have great performance, developed to meet all the needs of traders.

With maximum refrigeration expertise and design tradition, Derby can offer an incredible range of sizes and lid opening options that fit any point of sale. That is why it will always be the best option of Chest Freezer for your establishment.



• Adjustable thermostat

- Castors* Produce smooth and more controllable movement.
- Front pannel* For easy temperature read-out and control lamp.
- Highly hygienic
- Ideal storage for fast food outlets
- Integrated handle
- Internal light* Allowing good product visibility.
- Maximum storage space
- Stainless steel available*
- The perfect storage freezer
- Thermometer* Informs you about internal temperature.
- Wide assortment of baskets* Baskets with dividers allow good arrangement of the products.





HINGED LID

INTEGRATED HANDLE

STAINLESS STEEL

LID AVAILABLE*





* Options



www.derby.dk www.metalfriosolutions.com



DIMENSIONS
Capacity
Gross (liters / cubic feet)

Net (liters / cubic feet)

481 / 16.98

459/16.20

70

External dimensions	
Width (mm / inches)	1535 / 60.43
Height (mm / inches)	855 / 33.66
Depth (mm / inches)	730/28.74
Internal dimensions	
Width (mm / inches)	1380 / 54.33

width (mm / inches)	1380/54.33
Height* (mm / inches)	680 / 26.77
Depth (mm / inches)	530 / 20.86

14	Lai	~	
	eı	uı	н

VVEI	yn
Net	(kg)

* Not considered the compartment for the compressor.

TRANSPORTATION	
Packaging	
Width (mm / inches)	1550 / 61.02
Height (mm / inches)	960 / 37.79
Depth (mm / inches)	750 / 29.52
Loading container	
20 feet	-
40 feet	-

Piling up

Maximum

Weight Gross (kg)



F 58

5 10 **REAL SIZE** 1650mm 64.9 in

TEMPERATURE RANGE		
emperature range (°C)	-11 to -22	
emperature range (°F)	12.2 to -7.6	
Climate class	4 & 4+	
rechnology		
ype of evaporator	Aluminium	
Type of refrigeration agent (gas	s) R134A	
POWER		
/oltage / Frequency	230V / 50Hz	
/oltage / Frequency	-	
/oltage / Frequency	-	
Power (W)	168	
nergy consumption (KWh/24h	n) –	
MERCHANDISING AREA	Derby	
Sidewall	Front	
Width (mm) -	Width (mm) -	
Height (mm) -	Height (mm) -	

MARCH / 2009 - Images merely illustrative - Images and information subject to amendment with no prior notice.

Sidewall Width (mm) Height (mm)	-	Front Width (mm) Height (mm)	-
OPTIONS		-	
 Removable Baskets Quick Freezing		ai _igitt	astor hermometer

A Metalfrio Solutions

www.derby.dk www.metalfriosolutions.com

