

# HD15BT

-

### Freezer-GN2/1-anti-fingerprint-Shine Prime

One-piece structure in special anti-fingerprint steel. Single compartment, GN2/1. 2 doors. Temperature ranges: -20/-10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



CE

Refrigeration power at -30°C W	750
neral information	
Supplier/producer 's name	SAGI
Series	Shine Prime
Supplier's model identifier	HD15BT
Category	vertical cabinet
Туре	freezer
Line	catering - GN 2/1
hnical features	
Temperature ranges, °C	-20/-10
Energy Efficiency Class	F
Energy consumption, kWh/24h	17,6
Energy consumption/year, kWh/a	6424
Method for energy consumption	EN 16825
Energy Efficiency Index	94,55
Net usable volume, lt	1080
Volume, gross, lt	1180
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}$ C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,14

67

LWA dB(A)

ANGELO PO GRANDI CUCINE S.p.a. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it



Freezer-GN2/1-anti-fingerprint-Shine Prime

# HD15BT



Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,92

#### **Construction features**

Structure	one - piece structure with rounded internal corners
External material	special anti-fingerprint steel
Internal material	special anti-fingerprint steel
Insulation thickness, mm	75
Door	2 doors in special anti-fingerprint steel
Standard hinging door	on the right/reversible on the site with self-closing device for opening inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	21/60
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

### **Control and functions**

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical and acoustical

#### Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	24 plastic - coated hooks
Shelves (n.)	6, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	35
ensions and weights	
Packing (LxDxH), cm	154x85,5x207
Dimensions (LxDxH), cm	150x80x204
Gross Weight (kg)	219
Net Weight (kg)	199

