

1S0VTR



INFRARED PYROCERAM COOKING RANGE 4 AREAS



Electric range with pyroceram surface with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking surface in pyroceram, flush with worktop and sealed. Heating by infrared electric elements. 4 cooking independent areas controlled by energy regulator.



Power supply	Electricity	Product fitting up	Counter Top
Worktop thickness	2 mm		

Functional features

- Cooking surface in pyroceram, flush with worktop and sealed.
- n. 4 independent cooking areas power rated at 5 kW each
- Power regulator, 10 levels.
- Electronic diagnostic system with signaling alarm code through light on the controle console.
- Indirect cooking.
- Heating by incandescent heating elements.
- Easy to clean thanks to a smooth, hermetic glass ceramic surface.
- Commutable to 230V 3F 50/60 Hz
- Pre-set appliance for installation on under compartment, support surface; with specific accessories on bridge solution and cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Pyroceram glass, thickness 6 mm, max load weight: 0.2 kg/cm².
- Two glass surfaces with dimension each: 32 x 56 cm.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Non-slip rubber feet h = 2 cm.
- Access to all components through front compartment or control console.

Safety equipment and approvals

- Thermal protection for over temperature.
- Residual heat indicator light under glass.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX4 protection rating.

Technical Data

Working voltage	400V 3N ~ 50 ÷60 Hz	Electric Power	10 kW
Dimensions	80x72x25 cm	Packing	86x82x65 cm

INFRARED PYROCERAM COOKING RANGE 4 AREAS

Icon 7000 prof. 700



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90
web: www.angelopo.com - email: angelopo@angelopo.it

23/02/2021