

Аксессуары Автоматический водоумягчитель для печей

SIS # _____

AIA # _____



921305 (WASOAU)

Автоматический
водоумягчитель для печей

Характеристики

- The water softener has been designed specifically for convection and combi ovens and is suitable for all size of ovens, from 6 to 40 grids.
- Equipped with an electromechanical valve that allows regeneration from between once per day to once per week.
- Operating pressure between 2,8 and 5 bar.
- Maximum flow rate 1800lt/h
- Incorporates 8 litre cylinder in stainless steel 304 AISI with 5,6 litres of resin.
- Maximum salt content in brine of 20 kg. Every regeneration cycle requires 1kg of salt consumption
- Water connection between 4°C to 49°C.
- Quantity of soft water depending on hardness according to French regulation:
 - 30°- 2100 lt
 - 40°- 1900 lt
 - 50°- 1800 lt
 - 60°- 1700 lt
- Quantity of soft water depending on hardness according to German regulation:
 - 17°- 2100 lt
 - 22°- 1900 lt
 - 27°- 1800 lt
 - 33°- 1700 lt
- All models comply with the standards required by the main international approval bodies and are CE marked.

Одобрено _____

Электрика

Электропитание:

921305 (WASOAU) 220-230 V/1N ph/50/60 Гц

Вода

Мин.давление, бар: 2

Основная информация

Габариты, ширина: 250 мм

Габариты, высота: 540 мм

Габариты, глубина: 480 мм

Вес нетто: 12 кг

