## **KIBBA**

# JOGI

# REFRIGERATED COUNTER 390 lts., 70cm depth, -12/-24°C

Inside and outside in 18-10 stainless steel. One- piece structure, insulated doors. Cooling system with exterior finned evaporator, electric fan. Automatic condensation drain. Electronic card with Hyper Cold and Energy Saving functions. Automatic 'intelligent' defrosting. Radiused top 60 mm h, rear splashback. 3 doors.



 $\epsilon$ 

General in	form	ation
------------	------	-------

Supplier/producer 's name	SAGI
Series	ldea
Supplier's model identifier	KIBBA
Category	counter cabinet
Туре	freezer counter
Line	catering - GN 1/1

### **Technical features**

cillical leacules	
Temperature ranges, °C	-24/-12
Energy Efficiency Class	G
Energy consumption E24, kW/h	11,31
Energy consumption/year, kW/h	4126
Method for energy consumption	EN 16825
Energy Efficiency Index	108,9
Net usable volume, lt	241
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R452A/2141
Refrigerant charge, kg	0,57
LWA dB(A)	59
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic

REFRIGERATED COUNTER 390 lts., 70cm depth, -12/-24°C





# REFRIGERATED COUNTER 390 lts., 70cm depth, -12/-24°C

# **KIBBA**



Refrigeration power -23,3°C W	640	
Frequency/voltage	230V 1N~ / 50Hz 0,9	
Electric power, kW		
onstruction features		
Structure	one-piece structure with rounded internal corners	
External material	AISI 304 stainless steel	
Internal material	AISI 304 stainless steel	
Internal bottom	with rounded corners	
Insulation thickness, mm	60	
Internal structure	AISI 304 stainless steel grid-supporting rack	
Positions (n.)/spaced, mm	11/40,5	
Evaporator	with an anti-corrosion treatment	
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser	
Feet	stainless steel AISI 304, adjustable in height	
Height of feet, mm	140 ÷ 200	
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac	
Equipped with	3 doors	
ontrol and functions		
Kinf of control	electronic pannel control board	
Display	digital	
Functions/programs	Hyper Cold - Energy Saving - setting of the relative humidity to 75% or to 90%	
andard		
Key-lock	optional	
Shelf's dimensions, cm	32,5x53 GN1/1	
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio	
mensions and weights		
Packing (LxDxH), cm	192x76x100	
Dimensions (LxDxH), cm	185x70x98,5	
Gross Weight (kg)	162	



