### **KUC4M**

# JOGI

## Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body. Temperature ranges:  $0/+10^{\circ}$  C. Worktop 60 mm thick in AISI 304 stainless steel. Depth 70 cm. GN 1/1. With doors and drawers. Control panel with digital thermometer - thermostat.



 $\epsilon$ 

#### **General information**

Supplier/producer 's name	SAGI
Series	Universal
Supplier's model identifier	KUC4M
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

#### **Technical features**

Temperature ranges, °C	0/+10
Energy Efficiency Class	D
Energy consumption, kWh/24h	4,310
Energy consumption/year, kWh/a	1573
Method for energy consumption	EN 22041
Energy Efficiency Index	63,18
Net usable volume, lt	274
Volume, gross, It	578
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,08
LWA dB(A)	50
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-GN1/1-AISI 304-Universal







	Evaporation of condense drain	automatic
	Refrigeration power at -10°C W	560
	Frequency/voltage	230V 1N~ / 50Hz
	Electric power, kW	0,32
Co	nstruction features	
	Structure	one-piece structure with rounded internal corners
	External material	AISI 304 stainless steel
	Internal material	AISI 304 stainless steel
	Internal bottom	with rounded corners
	Insulation thickness, mm	60
	Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
	Internal structure	AISI 304 stainless steel grid-supporting rack
	Positions (n.)/spaced, mm	11/40,5
	Evaporator	with an anti-corrosion treatment
	Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
	Feet	stainless steel AISI 304, adjustable in height
	Height of feet, mm	140 ÷ 200
	Equipped with	doors and drawers
	Drawers, type: 1/2	4
Co	entrol and functions	
	Kinf of control	thermometer-thermostat
	Display	digital
	Alarms	optical
St	andard	
	Key-lock	optional
	Shelf's dimensions, cm	32,5x53 GN1/1
	Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
Di	mensions and weights	
	Packing (LxDxH), cm	235,5x75,5x90
	Dimensions (LxDxH), cm	230x70x90
	Gross Weight (kg)	198
	Net Weight (kg)	183

Refrigerated counter-GN1/1-AISI 304-Universal



