

Reference: LS28KB Service temperature wine cellar Service range



- Free standing installation
- → Design: black body & silver door frame
- + Cooling system: thermoelectric
- Type of cold: air moving system
- ♣ Adjustable temperature range of use: 11°C-18°C
- + Electronic regulation
- Thermometer with blue digital display
- ➡ White LED lights with switch button
- Humidity control: natural (hygrodynamy concept)
- ↑ 1 glass door, 2-layers tempered glass (transparent)

Integrated door panel control



Our products are manufactured in compliance with European environmental rules.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device.

This equipment is designed to be used in an ambient temperature between 16°C-32°C.

Alcohol abuse is dangerous for health, please consume in moderation.

*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 6 shelves. Adding shelves reduce considerably the total capacity

considerably the total capacity.

**Capacity given as an indication with 33cl cans and measured without shelves.



Reference: LS28KB Service temperature wine cellar Service range



> EQUIPMENTS INCLUDED

- 6 fixed wooden shelves (beech), wooden front (beech)
- 4 adjustable feet (height 0.7 cm)

> TECHNICAL CHARACTERISTICS

■ Energy class: B

■ Annual electrical consumption: 175 kWh

■ Climatic class: N (16°C-32°C)

Noise level: 39 dBVoltage: 220-240 VPower input: 70 W

■ Category: 10 - Multi-use and other refrigerating

> LOGISTIC DATAS

Gross dimensions (WxDxH cm) : $47 \times 54 \times 80,5$ Net dimensions (WxDxH cm) : $42 \times 49,5 \times 78,6$

Gross weight (kg) : 20.00

Net weight (kg) : 18.00

Full truck (pcs) : 0

Container (pcs) 20' : 126

40' : 264

40' : 264 40' HC : 312

Gencod 3541361805066

> COMPATIBLE ACCESSORIES

Only available in spare parts

Non-contractual pictures Last update: 13/03/2019