

FD7TPV



Refrigerator glass door-GN2/1-AISI304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Single compartment, GN2/1. 1 glass door. Temperature ranges: 0/+10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



General information

Supplier/producer 's name	SAGI
Series	Freezy Prime
Supplier's model identifier	FD7TPV
Category	display cabinet
Type	refrigerator
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	E
Energy consumption, kWh/24h	3,1
Energy consumption/year, kWh/a	1131,5
Method for energy consumption	EN 22041
Energy Efficiency Index	82,3
Net usable volume, lt	466
Volume, gross, lt	590
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,08
LWA dB(A)	38
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	406

Refrigerator glass door-GN2/1-AISI304-Freezy Prime

ANGELO PO GRANDI CUCINE S.p.a. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 01/08/2022 09.49.23



FD7TPV



Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,22

Construction features

Structure	one - piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel (door inner side and inner ceiling made of special anti-fingerprint steel)
Internal bottom	diamond treated bottom with drain hole
Insulation thickness, mm	75
Door	1 glass door
Standard hinging door	on the right/no-reversible on the site with self-closing device for openings inferior to 90°
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	21/60
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	yes
Lighting	LED lighting
Couple of guides (n.)	3 pair of AISI 304 stainless steel runners
Shelves (n.)	3, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	48

Dimensions and weights

Packing (LxDxH), cm	79x85,5x213
Dimensions (LxDxH), cm	75x80x204
Gross Weight (kg)	142
Net Weight (kg)	127

Notes

Notes	Models ...PV, installation allowed to an altitude up to 800 metres above the sea level
-------	--

Refrigerator glass door-GN2/1-AISI304-Freezy Prime

