

Glass and Dishwasher PROFI

Model: Profi FX-10B

Type	One Tank Glass and Dishwasher
Rack Size	500 x 500 mm 500 x 530 mm
Design	Front door machine, adjustable as undercounter model
Capacity	40 Racks/h / 720 Plates/h / 1440 Glasses/h
Voltage	400/50/3 (230/50/1)
Tank, Frame and Panels	Stainless steel 18/9
Wash result	According to DIN10512 section 7

Ready to install:

- fill and drain hoses
- power cord (400 V-connection)
- detergent dispenser
- rinse agent dispenser
- rinse pump
- drain pump
- non-return valve

Wash pump with smart start

Automatic Tank Fill

Multi-Phasing

Rack equipment

1 Plate Rack P-18-12

1 Universal Rack B-00-07

1 Cutlery Rack with 4 boxes 01-246175-1

Product Advantages

- **VISIOTRONIC-TOUCH control:**

colour touchscreen (displays text and graphic) in conjunction with single-button control and remaining cycle time indication.

- **WASHSMART APP:**

controlling your warewash operation with smart technology: status and messages, usage and operating costs, hygiene, service and consumables order

- **SENSO-ACTIVE resource management:**

constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum, in order to guarantee a fully hygienic wash result

- **2IN1 double rack system:**

two racks can be washed in a single wash cycle. One rack of cups can be washed underneath, while a second rack containing dishes and cutlery can also be washed above it. Thanks to the optimum use of the entire wash chamber the performance of the machine can be doubled

- **CLIP-IN wash and rinse arms:**

wash and rinse arms can be removed with one hand and without any tools

- **Intelligent data documentation:**

automatic recording of important operational data and consumptions and indication on the display

- **USB-interface:**

Comfortable download of operational data in form of a protocol via USB

- **GENIUS-X² fine filter system:**

advanced filter system with prewash function reduces detergent consumption up to 35%

- **Interlocked strainer:**

prevents operation without tank strainer

- **Optional refill signal:**

Monitors contents of external as well as integrated chemical containers

- **Hygiene programme:**

for removal of calcium carbonate and other deposits from wash chamber

Technical Data:

Machine housing width	600 mm
Machine housing Depth	603 mm
Depth when Door is open	1048 mm
Height	825 mm
Loading height	425 mm
Cycle time**	90 / 180 / 360 sec. and special programs
Capacity**	Up to 40 Racks/h / 720 Plates/h / 1440 Glasses/h
Wash temperature	63 °C
Rinse temperature	82 °C
Tank capacity	10,6 l
Fresh water consumption/Rack	2 l
Booster loading	6,2 kW (2,1 kW)
Total loading	6,8 kW (2,7 kW)
Pump power	0,5 kW / 350 l/min
-	3x16 A (16 A)
Voltage	400/50/3 (230/50/1)

* To reach set rinse temperatures even with cold water connection, the actual cycle-times extend accordingly.

** Theoretical performance

